

# GLOSSARY

## ANCHOR

A device by which grating is attached to its supports.

## BAND

A flat bar welded to the end of a grating panel, or along the line of a cutout, and extending neither above nor below the bearing bars.

**Load-Carrying Band:** A band used in a cutout to transfer the load from unsupported bearing bars in the cutout to the supported bearing bars.

**Trim Band:** A band which carries no load, but is used chiefly to improve appearance.

## BEARING BARS

Load-carrying bars made from steel strip or slit sheet or from rolled or extruded aluminum and extending in the direction of the grating span.

## BEARING BAR CENTERS

The distance center to center of the bearing bars.

## CARRIERS

Flats or angles which are welded to the grating panel and nosing of a stair tread and are bolted to a stair stringer to support the tread.

## CLEAR OPENING

The distance between faces of bearing bars in a rectangular grating, or between a bent connecting bar and a bearing bar in a riveted grating.

## CROSS BARS

The connecting bars, made from steel strip, slit sheet, or rolled bars, or from rolled or extruded aluminum, which extend across the bearing bars, usually perpendicular to them. They may be bent into a corrugated or sinuous pattern and, where they intersect the bearing bars, are welded, forged or mechanically locked to them.

## CROSS BAR CENTERS

The distance center to center of the cross bars.

## CURVED CUT

A cutout following a curved pattern.

## CUTOUT

An area of grating removed to clear an obstruction or to permit pipes, ducts, columns, etc. to pass through the grating.

## ELECTRO-FORGED

A process combining hydraulic pressure and heat fusion to forge bearing bars and cross bars into a panel grid.

## END DIMENSION

The distance from an end of grating to center of first cross rod (except welded Heavy Duty, where distance is from edge of grating to back of first cross rod).

## FILLER BAR

A bar welded between two support bearing bars to close the spacing.

## FINISH

The coating, usually painted or galvanized which is applied to the grating.

## FLUSH TOP GRATING

A type of pressure-locked grating in which the cross bars and bearing bars are in the same plane relative to the top surface of the grating.

## GRATING

An open grid assembly of metal bars, in which the bearing bars, running in one direction, are spaced by rigid attachment to cross bars running perpendicular to them or by bent connecting bars extending between them.

## HINGED PANELS

Grating panels which are hinged to their supports or to other grating parts.

## I-BAR

An extruded aluminum bearing bar having a cross sectional shape resembling the letter "I".

## INTERLOCKING GRATING

Plank Grating – Snap Lock Plank grating with male and female sides that lock together.

# GLOSSARY

## **INTERSECTION AREA**

The point where the bearing bar and cross bar intersect or cross. In heavy duty grating with a rectangular cross bar; an intersection has four (4) sides.

## **LENGTH**

The dimension of a grating panel measured parallel to the bearing bars. Also referred to as span.

## **MARKING**

(Mark Number) Used to identify each unique piece.

## **NOSING**

A special L-section member serving as the front or leading edge of a stair tread, or of grating at the head of a stair.

## **NOTCHED BAR**

A cut out in the bearing bar. A burn out or punch.

## **PRESSURE-LOCKED GRATING**

Pressure-locked means bearing bars are locked in position by cross bar deformation instead of riveting or welding.

Several proven methods are:

- Expansion of an extruded or drawn tubular cross bar
- Extruded cross bar deformed or swaged between bearing bars
- Press assembly of rectangular cross bars into slotted bearing bars.

## **RADIALLY CUT GRATING**

Rectangular grating which is cut into panels shaped as annular segments, for use in circular or annular areas.

## **RETICULINE BAR**

A sinuously bent connecting bar extending between two adjacent bearing bars, alternately contacting and being riveted to each.

## **RIVET CENTERS**

The distance center to center of rivets along one bearing bar.

## **RIVETED GRATING**

Grating composed of straight bearing bars and bent connecting bars, which are joined, at their contact points, by riveting.

## **SERRATED GRATING**

Grating which has the top surfaces of the bearing bars or cross bars, or both, notched.

## **SKEW CUT**

A fabricated diagonal cut.

## **SPAN OF GRATING**

The distance between points of grating support, or the direction of this dimension. Also referred to as length.

## **STRAIGHT CUT**

That portion of the cut edge or cutout of a grating which follows a straight line.

## **SWAGING**

A method of altering the cross-sectional shape of a metal bar by pressure applied through dies.

## **TOE PLATE**

A flat bar attached against the outer edge of a grating or rear edge of a tread, and projecting above the top surface of grating or tread to form a lip or curb.

## **TREAD**

A panel of grating having carriers and nosing attached by welding, and designed specifically to serve as a stair tread.

## **WELDED GRATING**

Grating in which the bearing bars and cross bars are joined at all of their intersections by either a resistance weld or conventional hand welding.

## **WIDTH**

The overall dimension of a grating panel, measured perpendicular to the bearing bars, and in the same direction as the cross bars.