



OHIO GRATINGS, INC. PRESENTS OUR

KWIK SHIP PROGRAM

WHEN GRATING ABSOLUTELY
HAS TO BE THERE!

Featuring the following products for shipment in 1 to 3 days!

- Carbon Steel Panels
- Stainless Steel Panels (3 days)
- Aluminum Panels
- Treads
- Light Fabrication

ALUMINUM & CARBON STEEL PANELS

- Widths 2' and 3'
 - Lengths 6', 8', 10', 12', 20' and 24'
- (See back for details)*

ALUMINUM & LIGHT DUTY CARBON STEEL TREADS

- Aluminum and custom steel sizes with quantities up to 25
 - Stock Steel Treads with 9 sizes available and quantities up to 50
- (See back for stock sizes)*

CUT PIECES & LIGHT FABRICATION

- Cut pieces up to 900 sq. ft.
- Lengths as required
- Fabrication: straight, skew and circle cuts, nosings and trim band

FINISHES AVAILABLE

- Carbon Steel - Mill, Shop Black & Galvanized *(Add 2 additional days for galvanizing)*
- Aluminum - Mill
- Stainless Steel - Mill

NEW!

#304 SWAGED STAINLESS STEEL PANELS

- Widths 2' and 3'
- Lengths 8', 10' and 12'
- Heights 1", 1-1/4" and 1-1/2"
- Smooth surface
- Other configurations available

**NOW AVAILABLE
IN 3 DAYS!**



OHIO GRATINGS, INC.



KWIK SHIP PROGRAM

AVAILABLE PRODUCTS

- 19W4 Light Duty Carbon Steel (smooth surface, 1/8" thick) 1", 1-1/4", 1-1/2"
(serrated is not available)
- 19W4 Light Duty Carbon Steel (smooth or serrated surface, 3/16" thick) 1", 1-1/4", 1-1/2", 1-3/4", 2"
- 19SG4 Swaged Aluminum (smooth surface, 3/16" thick)..... 1", 1-1/4", 1-1/2", 1-3/4", 2"
(serrated surface available in 1", 1-1/4" and 1-1/2" only)
- 19SGI4 Swaged Aluminum I-Bar..... 1", 1-1/4", 1-1/2", 1-3/4", 2"

STOCK TREADS - (LIGHT DUTY STEEL)

<u>BEARING BAR</u>	<u>WIDTH</u>	<u>LENGTH</u>	<u>SPACING</u>
1" x 3/16"	9-3/4"	2'-6"	19W4
1" x 3/16"	12-1/8"	2'-6"	19W4
1" x 3/16"	10-15/16"	3'-0"	19W4
1" x 3/16"	12-1/8"	3'-0"	19W4
1-1/4" x 3/16"	9-3/4"	2'-6"	19W4
1-1/4" x 3/16"	10-15/16"	2'-6"	19W4
1-1/4" x 3/16"	9-3/4"	3'-0"	19W4
1-1/4" x 3/16"	10-15/16"	3'-0"	19W4
1-1/4" x 3/16"	12-1/8"	3'-0"	19W4

Black finish available per NAAMM Standards. One shop coat of manufacturer's standard paint which is designed to protect the grating from the elements during transit only.

Galvanized finish available per NAAMM Standards. Gratings specified to be galvanized shall have their exposed surfaces zinc-coated by the hot dip process after fabrication, with a coating of not less than 1.8 oz/sf of coated surface per ASTM123.

WE CAN GET IT THERE... **FAST!**

5299 Southway SW • Canton, OH 44706 • Toll Free: 800-321-9800 • Fax: 330-477-7872
E-mail: info@ohiogratings.com • Visit us online at www.ohiogratings.com